

Shaft alignment system

Easy-Laser XT440

Easy alignment with maximum flexibility

The Easy-Laser XT440 is the first alignment system of the new XT generation. This shaft alignment system is platform independent and can therefore also be used with iOS and Android devices. The Easy-Laser XT440 is very robust, waterproof and dustproof (IP66/IP67). To make this new generation Easy-Laser as user-friendly as possible, all XT measuring programs have been collected in a single user-friendly app that can be downloaded for free.

- Able to align shafts both horizontally and vertically!
- The app works on your iOS or Android phone or tablet.
- No licenses. The measuring units determine which measurements can be carried out.
- Saves measurements.
- Possibility to save notes and photos.
- Information can be shared with your customer by email.
- The XT products are very robust, waterproof and dustproof (IP66/IP67).
- Long battery life.
- Use in combination with XT190.

Optional:

- XT12 display
- XT12 display with integrated thermal camera

Type	Easy Laser XT440
Art. no.	780320
Dimensions LxWxH	460 x 350 x 175 mm
Weight incl. all parts	7.2 kg

Sensor unit M/S

Detector	True PSD 30 mm
Connection	Bluetooth
Measurement accuracy	< 1 % / up to 10 m
Laser type / Laser class	Diode laser / Safety class II
Casing material	Anodised alu PC/ABS + TPE
Dimensions LxWxH	76 x 76.7 x 39.3 mm
Weight	245 g

Type	XT12 display
Art. no.	780319
Art. no. (With IR camera)	780318

Display unit XT12

Operating temperature	-10 to 50°C / 14 to 122 °F
Display	VGA 8" colour display, LED
Power / Operating time	Heavy duty Li Ion rechargeable / 16 hours
Connection	WiFi
Casing material	PC/ABS + TPE
Dimensions LxWxH	274 x 190 x 44 mm
Weight	1,450 g
Cable (loading)	Splitter 1 m
Brackets (chain)	V bracket for chains, width 18 mm, shaft diameter 20-150 mm
Rods	120 mm, 60 mm extendable / Stainless steel



Complete system

- 1 measuring unit XT40-M
- 1 measuring unit XT40-S
- 2 measuring units (M & S)
- 2 chain brackets with rods
- 4 rods, 60 mm
- 1 tape measure, 3 m
- 1 hex key set
- 1 charger (100-240V AC)
- 1 DC splitter cable
- DC-USB adapter, for charging
- 1 quick-start manual
- USB with manuals
- 1 carrying case

