



	Handheld Indicator	SPARE CODE	INDIGO80	1	2	3	4	5	6	7	8
hardware	1 Power Supply Unit	USB Cable, no PSU		A							
		Rechargeable with Euro AC-adapter		B							
		Rechargeable with UK AC-adapter		C							
		Rechargeable with US AC-adapter		D							
		Rechargeable with AUS AC-adapter		E							
accessory	2 Indicator Accessories	No Accessories		O							
		• <i>Magnetic hanger for Indigo80 handheld indicator</i>	<i>ASM214318SP</i>								1
	3 Connection Cables for Transmitters	No Connection Cables for Transmitters		N							
		• <i>M12-M8 Service Cable</i>	<i>262195SP</i>								A
	4 Connection Cables for Probes	No Connection Cables for Probes		O							
	• <i>M12-M12 Probe Connection Cable</i>	<i>272075SP</i>									1
	• <i>Flat Cable</i>	<i>CBL210493SP</i>									2
hw	5 Carrying Case	No Carrying Case		N							
		• <i>Weatherproof Carrying Case</i>	<i>ASM214759</i>								A
	6 Indicator color	Housing option color grey									1
	Housing option color black										2
7 Other Options	No Other Options										N
	Japanese SW Version										A

NOTE: Selections in bold are included in the prices of the basic versions.
• Selections in *italic* are available at an extra price.

LINKS: [User Guides](#)
[Datasheet](#)
[Vaisala.com product page](#)

Example of order code with typical settings:
INDIGO80 **A** **7** **N** **O** **A** **1** **N** **O**

Related Items

USB Service Cable M12-5F, RS-485
Cable, Spare Part M12/5(M)-M12/5(F), 5x0.34mm², 1.5m, PP/PUR, BLK
Magnetic Hanger Spare Part
Indigo80 Case Packaging
Flat Cable, M12-5(M) - M12-5(F), 1m
Probe Connection Cable (M12-M12), 10 m

Part number

242659
272075SP
ASM214318SP
ASM214759
CBL210493SP
INDIGOCABLE10M

HMP80 Handheld Humidity Probe



		Handheld Humidity Probe		SPARE CODE	HMP80	1	2	3	4	5	6
accessor	1	Probeset	Probe (106 mm) with HUMICAP R2C Sensor ¹ Long probe (319 mm) with HUMICAP R2C Sensor ²			N					
						L					
hardware	2	Probe connection cables	No Cable				O				
			• <i>M12-M12 Probe Connection Cable</i>	<i>272075SP</i>				<i>1</i>			
			• <i>Flat probe connection cable</i>						<i>2</i>		
		3	Filter	Sintered Stainless Steel Filter ²	<i>HM47280SP</i>						A
				Plastic PPS Grid Filter ²	<i>DRW010276SP</i>						B
			PPS Grid With SS Netting ²	<i>DRW010281SP</i>						C	
			Slotted MIM Filter with Membrane ¹	<i>DRW255306SP</i>						D	
			Slotted MIM Filter with Membrane ¹	<i>ASM214606SP</i>						E	

- 1) These filters fit the short probe
2) These filters fit the long probe

NOTE: Selections in bold are included in the prices of the basic versions.
• Selections in italic are available at an extra price.

LINKS: [User Guides](#)
[Datasheet](#)
[Vaisala.com product page](#)

Example of order code with typical settings:

		1	2	3	4	5	6
HMP80		N	7	E	1	S	O

Related Items

Cable, Spare Part M12/5(M)-M12/5(F), 5x0.34mm², 1.5m, PP/PUR, BLK
Slotted MIM Filter with Membrane Spare Part
Flat Cable, M12-5(M) - M12-5(F), 1m
PPS Plastic Grid Filter
Metal Coated PPS Grid Filter with Stainless Steel Mesh, Female Thread
Slotted MIM Filter Spare Part
Sintered Stainless Steel Filter, Female Thread
Indigo-compatible USB Adapter

Part number

272075SP
ASM214606SP
CBL210493SP
DRW010276SP
DRW010281SP
DRW255306SP
HM47280SP
USB2

DMP80 Handheld Dew Point Probe



Handheld Dew Point Probe		SPARE CODE	DMP80	1	2	3	4	5	6	7	8
hardware	1 Probeset	Probe with Range [-40...+60°C Td], DRYCAP®180S Sensor	A								
		Probe with Range [-70 ... +60°C Td], DRYCAP®180M sensor	B								
accessory	2 Thread	Mechanical connection, ISO G1/2" thread	G								
		Mechanical connection, NPT 1/2" thread	N								
	3 Probe connection cables	No Cable	0								
		• <i>M12-M12 Probe Connection Cable</i>		1							
		• <i>Flat probe connection cable</i>		2							
5 Accessories for ISO G1/2" thread	Accessories for ISO G1/2" thread option	0									
	• <i>Sampling Cell with Quick Connector and Leak Screw (DSC74)</i>		1								
	• <i>Sampling Cell with Female Connectors, Inlet G3/8", Outlet G1/4" ISO</i>		2								
	• <i>Sampling Cell with Swagelok Connectors for 1/4" Tubing (DMT242SC2)</i>		3								
	• <i>Two-Pressure Sampling Cell (DSC74B)</i>		4								
	• <i>Two-Pressure Sampling Cell with Coil (DSC74C)</i>		5								

NOTE: Selections in bold are included in the prices of the basic versions.
• Selections in *italic* are available at an extra price.

LINKS: [User Guides](#)
[Datasheet](#)
[Vaisala.com product page](#)

Example of order code with typical settings:
DMP80 B G 7 A O A S O

Related Items

Cable, Spare Part M12/5(M)-M12/5(F), 5x0.34mm2, 1.5m, PP/PUR, BLK
Flat Cable, M12-5(M) - M12-5(F), 1m
Sampling Cell DMT242SC with Female Connectors, inlet G3/8" & outlet G1/4" ISO
Sampling Cell DMT242SC2 with Swagelok Connectors for 1/4" Tubing
Sampling Cell with Quick Connector and Leak Screw
Two Pressure Sampling Cell
Two Pressure Sampling Cell with Coil
Sintered Stainless Steel Filter, Female Thread
Indigo-compatible USB Adapter

Part number

272075SP
CBL210493SP
DMT2425C
DMT2425C2
DSC74
DSC74B
DSC74C
HM47280SP
USB2

GMP252 CO2 Probe for ppm Measurements



CO2 Probe for ppm Measurements		SPARE CODE	GMP252	1	2	3	4	5	6	7	8
ACCESSORY	6 Cable	No Cable		6	1	C	0	B	H	3	
		• <i>M12-M12 Probe Connection Cable (Indigo80)</i>									0
		• <i>Flat Probe Connection Cable (Indigo80)</i>									8
											9

NOTE: Selections in bold are included in the prices of the basic versions.
• Selections in italic are available at an extra price.

LINKS: [User Guides](#)
[Datasheet](#)
[Vaisala.com product page](#)

Example of order code with typical settings:

GMP252	1	2	3	4	5	6	7	8
GMP252	6	1	C	0	B	H	3	

Related Items

- USB Service Cable M12-5F, RS-485
- Probe Mounting Clips (2 pcs)
- Probe Mounting Flange
- Connection Cable, M12-5F 90° - Open Wires, 0.6 m
- Mounting flange for GMP251 and GMP252
- Cable, Spare Part M12/5(F)-Open, 5x0.34mm2, 1.5m, PP-EPDM/PP, GRY
- Cable, Instrumentation, SH, M12/5(F) RA-Open, 5x0.34mm2, 1.5m, PP/PUR, HF, BLK
- Connection Cable, M12-5F - Open Wires, 3 m
- Flow Through Adapter Assembly GMP252 Spare Part
- Spray Shield (IPX9 Rating)
- Flat Cable, M12-5(M) - M12-5(F), 1m
- Porous Sintered PTFE Filter, Extra Protection
- Calibration Adapter
- Radiation Shield for Outdoor Use
- Radiation Shield with Mast Installation Kit
- Indigo-compatible USB Adapter
- Connection Cable, M12-5F - Open Wires, 10 m
- Connection Cable, M12-5F - Open Wires, 1.5 m

Part number

- 242659
- 243257SP
- 243261SP
- 244669SP
- 252346SP
- 254294SP
- 255102
- 26719SP
- ASM212011SP
- ASM212017SP
- CBL210493SP
- DRW244221SP
- DRW244827SP
- DTR250
- DTR250A
- USB2
- 216546SP
- 223263SP