

QTG60ML

Ø60mm LED Steady/Flashing Tower Lights



QTG60ML series



QTGA60ML series

• Customization



- High buzzer module equipped on top/ Black housing tower lights.

QTG60ML Ø60mm Direct Mount, LED Steady/Flashing Type

Model number	Layer	Voltage	Current	Certificates	Weight	Color
QTG60ML Steady	1	AC/DC12V	0.090A	CE DC only UL DC24V only	0.26kg	• R-Red
QTG60ML-BZ Steady /w built-in buzzer		AC/DC24V	0.050A		0.26kg	
QTG60MLF Steady/Flashing	2	AC/DC12V	0.180A		0.34kg	• R-Red • G-Green
QTG60MLF-BZ Steady/Flashing /w built-in buzzer		AC/DC24V	0.100A		0.34kg	
QTGA60ML Steady	3	AC/DC12V	0.270A		0.43kg	• R-Red • A-Amber • G-Green
QTGA60ML-BZ Steady /w built-in buzzer		AC/DC24V	0.150A		0.43kg	
QTGA60MLF Steady/Flashing	4	AC/DC12V	0.360A		0.51kg	• R-Red • A-Amber • G-Green • B-Blue
QTGA60MLF-BZ Steady/Flashing /w built-in buzzer		AC/DC24V	0.200A		0.51kg	
QTG60MLF Steady/Flashing	5	AC/DC12V	0.450A		0.59kg	• R-Red • A-Amber • G-Green • B-Blue • W-White
QTG60MLF-BZ Steady/Flashing /w built-in buzzer		AC/DC24V	0.250A		0.59kg	

* AC type model has a free-voltage range of 100V-240V.

Signal/ Audible Line Current(per each layer)

Voltage	AC/DC12V	AC/DC24V	AC110V-220V
Signal line current	0.090A	0.050A	Max 0.050A
Audible line current	0.016A	0.031A	Max 0.030A

Wiring Instructions

- External power line standard : UL1015 AWG18(0.75sq)×2C 400mm
 - Signal line standard : UL1007 AWG22(0.3sq) 400mm
 - LED tower light can be wiring with external contact and transistor
- * Please refer to page 323-324 for detailed wiring instructions.

Customization

- High buzzer module equipped on top(Lens should be within 4 layers)
- Black housing tower lights
- 2 buzzer sound types : Both prolonged (beep, beep) and staccato (beep, beep, beep) buzzer output available
- Wall mount bracket options : Bracket structure allows for threading through the bracket hole or into the wall mount



Ordering Specification

QTG60ML	3	24	RAG
[Model number]	[Layer]	[Voltage]	[Color]
<ul style="list-style-type: none"> • QTG60ML • QTG60ML-BZ • QTG60MLF • QTG60MLF-BZ • QTGA60ML • QTGA60ML-BZ • QTGA60MLF • QTGA60MLF-BZ 	<ul style="list-style-type: none"> • 1-1Layer • 2-2Layers • 3-3Layers • 4-4Layers • 5-5Layers 	<ul style="list-style-type: none"> • 12-DC12V • 24-DC24V • 110/220 -AC110V-220V 	<ul style="list-style-type: none"> • R-Red • A-Amber • G-Green • B-Blue • W-White

QTG60L

Ø60mm LED Steady/Flashing Tower Lights



QTG60L series



QTGA60L series

• Customization



- High buzzer module equipped on top/ Black housing tower lights.

QTG60L Ø60mm Pole Mount, LED Steady/Flashing Type

Model number	Layer	Voltage	Current	Certificates	Weight	Color	
QTG60L Steady	1	AC/DC12V	0.090A	CE DC only UL DC24V only	0.41kg	• R-Red	
QTG60L-BZ Steady /w built-in buzzer		AC/DC24V	0.050A		0.41kg		
QTG60LF Steady/Flashing	2	AC/DC12V	0.180A		0.50kg	• R-Red • G-Green	
QTG60LF-BZ Steady/Flashing /w built-in buzzer		AC/DC24V	0.100A				0.60kg
QTGA60L Steady		AC/DC12V	0.270A				0.58kg
QTGA60L-BZ Steady /w built-in buzzer	AC/DC24V	0.150A					
QTGA60LF Steady/Flashing	4	AC/DC12V	0.360A		0.67kg	• R-Red • A-Amber • G-Green • B-Blue	
QTGA60LF-BZ Steady/Flashing /w built-in buzzer		AC/DC24V	0.200A				0.77kg
QTGA60LF-BZ Steady/Flashing /w built-in buzzer		AC/DC12V	0.450A				0.75kg
	AC/DC24V	0.250A	0.85kg				
	5	AC110V-220V	Max 0.138A				

* AC type model has a free-voltage range of 100V-240V.

Wiring Instructions

- External power line standard : UL1015 AWG18(0.75sq)×2C 400mm
- Signal line standard : UL1007 AWG22(0.3sq) 400mm
- LED tower light can be wiring with external contact and transistor

* Please refer to page 323-324 for detailed wiring instructions.

Mounting Bracket

Standard	LB18	LW18	QZ18	SZ18	QL18	SL18	QLA18
Steel	Steel	PC	PC	Al	PC	Al	PC

* Please refer to page 32-37 for detailed dimensions.

Customization

- 2 buzzer sound types : Both prolonged (beep, beep) and staccato (beep, beep) buzzer output available
- Customized pole length available
- High buzzer module equipped on top(Lens should be within 4 layers)
- Black housing tower lights

Ordering Specification

QTG60L	-	3	-	110/220	-	RAG	-	LW18
[Model number]		[Layer]		[Voltage]		[Color]		[Mounting bracket]
<ul style="list-style-type: none"> • QTG60L • QTG60L-BZ • QTG60LF • QTG60LF-BZ • QTGA60L • QTGA60L-BZ • QTGA60LF • QTGA60LF-BZ 		<ul style="list-style-type: none"> • 1-1Layer • 2-2Layers • 3-3Layers • 4-4Layers • 5-5Layers 		<ul style="list-style-type: none"> • 12-DC12V • 24-DC24V • 110/220 • -AC110V-220V 		<ul style="list-style-type: none"> • R-Red • A-Amber • G-Green • B-Blue • W-White 		<ul style="list-style-type: none"> • None -Standard • Bracket -LB18 -LW18 -QZ18 -SZ18 -QL18 -SL18 -QLA18